



UPC-MARATHON

OPERATIONS MANUAL

MATERIAL SAFETY DATA SHEET WAUKEE FLO-METER™ OIL

CONNECT WITH US



MASTERING
STRENGTH.
WORLDWIDE.



MANUAL #: 019

Revision #	Revision Date	Revision Description
002	August 4, 2020	Updated all sections with new product data
001	June 30, 2015	

THIS MANUAL IS SUPPLIED ELECTRONICALLY.

COPYRIGHT^(C)

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual, or otherwise, without prior written permission of United Process Controls Inc. (UPC-Marathon).

The information contained in this document is **STRICTLY CONFIDENTIAL** and **PROPRIETARY** to UPC-Marathon, and shall not be: i) reproduced or disclosed in part or in whole, ii) used for any design or manufacturing of heat treating and/or control equipment, or any other purpose except for that which it is supplied under the terms of the Contract, unless the express written authorization is obtained from UPC-Marathon.

Drawings and photographs included in the documentation are the property of UPC-Marathon, and it is strictly forbidden to reproduce them, transmit them to a third party, or use them for manufacturing and/or design of equipment. Sub-licensing of any technical information contained in this Documentation is strictly forbidden under the terms of the Contract.

UPC-Marathon reserves the right to modify this document without prior notice.

DISCLAIMER:

The information provided in this Safety Data Sheet is based on our current knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

WARRANTY:

UPC-Marathon warrants its goods as being free of defective materials and faulty workmanship. Contact your local sales office for warranty information. If warranted goods are returned to



UPC-Marathon during the period of coverage, UPC-Marathon will repair or replace without charge those items it finds defective. The foregoing is Buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

TECHNICAL ASSISTANCE

For all questions or concerns regarding the proper use of Waukee Flo-Meter™ Oil, please consult the last page of this manual for contact information.



Table of Contents

1	PRODUCT AND COMPANY IDENTIFICATION	5
2	HAZARDS IDENTIFICATION	5
3	COMPOSITION/INFORMATION ON INGREDIENTS	6
4	FIRST AID MEASURES	6
5	FIRE FIGHTING MEASURES.....	7
6	ACCIDENTAL RELEASE MEASURES.....	7
7	HANDLING AND STORAGE	8
8	EXPOSURE CONTROLS/PERSONAL PROTECTION.....	9
9	PHYSICAL AND CHEMICAL PROPERTIES	10
10	STABILITY AND REACTIVITY	11
11	TOXICOLOGICAL INFORMATION	11
12	ECOLOGICAL INFORMATION	12
13	DISPOSAL CONSIDERATIONS	12
14	TRANSPORT INFORMATION.....	13
15	REGULATORY INFORMATION.....	13
16	OTHER INFORMATION	15
17	CUSTOMER SUPPORT	15

1 PRODUCT AND COMPANY IDENTIFICATION

Product Name: Waukee Flo-Meter™ Oil
Product Code: FOIL-1, FOIL-2, FOIL-3, FOIL-4, FOIL-5, FOIL-6

Manufacturer or supplier's details

Lubrication Technologies, Inc.
900 Mendelssohn Avenue North
Golden Valley, MN 55427-4309
United States

Emergency telephone CHEMTREC: 1-800-424-9300
Poison Control Center: Consult local telephone directory for emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use: Flo-Meter™ Float Rod Dampening
NSF 3H and H1 Registered.
This product complies with FDA 21 CFR 172.878 "White Mineral Oil" and 21 CFR 178.3620(a) regulations for direct food contact.

2 HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Clear
Odor	Odorless.

GHS Classification

Aspiration hazard: Aspiration toxicant category 2
Target organs: Lungs

GHS Label element

Hazard pictograms:



Signal word: Warning

Hazard statements: H305 - May be harmful if swallowed and enters airways



Other Hazards:	Not determined.
Prevention:	None required.
Response:	P331 - Do NOT induce vomiting P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Storage Procedures:	P405 - Store locked up
Disposal:	P501 - Dispose of contents and container in accordance with federal, state, and local regulations
Other:	See section 11 Toxicological Information for complete health hazard information.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Percentage by Weight
White mineral oil	8042-47-5	100 %

The balance of components does not contribute to the overall classification of the fluid, according to the GHS Standard.

4 FIRST AID MEASURES

Eye contact:	If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.
Skin contact:	Call a doctor if you feel unwell.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.
Other:	No additional information.



5 FIRE FIGHTING MEASURES

Flash point: 171°C by Cleveland Open Cup Tester

Flammable limits: Not determined

Extinguishing media: Use dry chemical, alcohol foam, all-purpose AFFF or carbon dioxide to extinguish fire.

Special firefighting procedures: DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Unusual fire & explosion hazards: Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.

Byproducts of combustion: Fires involving this product may release oxides of carbon, phosphorus, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.

Autoignition temperature: Not determined

Explosion data: Not determined. Care should always be exercised in dust/mist areas.

Other: Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6 ACCIDENTAL RELEASE MEASURES

Spill control procedures (land): Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials



(sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. Clean up residue with an appropriate solvent. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact CHEMTREC at 1-800-424-9300.

Spill control procedures (water): Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 1-800-424-8802).

Waste disposal method: Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14 Transport Information.

Other: CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

7 HANDLING AND STORAGE

Handling procedures: Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.
Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns.
Open containers carefully in a well-ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.

Storage procedures: Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive



temperatures may produce odorous and toxic fumes from product decomposition.

Additional information: No additional information

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

	OSHA TWA	OSHA STEL	ACGIH TWA
Contains highly refined petroleum oil	*5 mg/m ³ (PEL)	*10 mg/m ³	*5 mg/m ³ (TLV)

* Exposure limits not defined. Limits used are for "oil mist".

TWA – Time Weighted Average is the employee’s average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

STEL – Short Term Exposure Limit is the employee’s 15-minute time weighted average exposure which shall not be exceeded at any time during a workday unless another time limit is specified.

All base oils, including additive carriers, contain <3.0% DMSO extractable material.

Personal protection: Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

Respiratory protection: None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

Eye protection: Eye protection is strongly recommended. Wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection: Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

Other protection: Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended



based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear
Odor:	Odorless
Odor Threshold:	Not determined
pH:	Not application
Melting/Freezing point:	Pour point: -10°F
Initial boiling point:	560°F
Boiling point:	Not determined
Flash Point:	171°C.
Evaporation rate:	Negligible
Flammability:	Not determined
Upper flammable limit:	Not determined
Lower flammable limit:	Not determined



Vapor pressure:	<0.1 mm Hg at 68°F
Vapor density:	>1
Relative density:	0.84
Solubility:	Negligible in water, miscible in most petroleum solvents.
Partition coefficient:	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	7.4 cSt at 40°C
Other:	Not applicable

10 STABILITY AND REACTIVITY

Reactivity:

Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors.
Other:	Not applicable

11 TOXICOLOGICAL INFORMATION

Chronic toxicity:



Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer
Reproductive toxicity:	Not expected to have adverse effects on reproduction
STOT-single exposure:	Not expected to have adverse effects
STOT-repeated exposure:	Not expected to have long term adverse effects
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

12 ECOLOGICAL INFORMATION

Eco toxicity:

Fish:	> 100 mg/l.
Invertebrates:	> 100 mg/l.
Aquatic plants:	> 100 mg/l.
Microorganism:	> 100 mg/l.

Persistence/Degradability: This product is not expected to be readily biodegradable.

Bioaccumulation: Not determined

Mobility in soil: Not determined

Other: All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

13 DISPOSAL CONSIDERATIONS



Waste disposal: This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product into sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.

Other: The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

14 TRANSPORT INFORMATION

Land Transport (DOT): Not regulated for land transport.

Proper Shipping Name: Not applicable.

Land Transport (TDG): Not regulated for land transport.

Proper Shipping Name: Not applicable.

Sea Transport (IMDG): Not regulated for land transport.

Proper Shipping Name: Not applicable.

Air Transport (IATA): Not regulated for land transport.

Proper Shipping Name: Not applicable.

Other: Not applicable.

15 REGULATORY INFORMATION

Federal Regulation

Clean water act/oil: Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or



film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported. Contact the National Response Center at 800-424-8802.

TSCA: All components of this material are listed in the U.S. TSCA Inventory.

Other TSCA: Not applicable

SARA title III: Section 302/304 extremely hazardous substances:
None.

Section 311, 312 hazard categorizations:

Acute (immediate health effects):	NO
Chronic (delayed health effects)	NO
Fire (hazard):	NO
Reactivity (hazard):	NO
Pressure (sudden release hazard):	NO

Section 313 toxic chemicals:

No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.

CERCLA: For stationary/moving sources – reportable quantity (due to):
Not hazardous due to the petroleum exclusion.

State Regulations

Right-to-know: Not determined.

Other: A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15 Regulatory Information. Failure to report may result in substantial civil and criminal penalties. Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.



16 OTHER INFORMATION

	NFPA 704	NPCA-HMIS
Health:	1	1
Fire:	1	1
Reactivity:	0	0
Specific hazard:	None	N/A
Protection index:	N/A	B

17 CUSTOMER SUPPORT

Americas	Asia	Europe
support.na@group-upc.com	service@mmichina.cn	support.eu@group-upc.com
USA: +1 414 462 8200	Shanghai: +86 21 3463 0376	France: +33 3 81 48 37 37
Canada: +1 514 335-7191	Beijing: +86 10 8217 6427	Germany: +49 7161 94888-0
		Poland: +48 32 296 66 00